

MAXIMUM

ACRYLIC FLOOR FINISH

Product # 020

DESCRIPTION

MAXIMUM is an acrylized floor finish detergent resistant, dirt resistant, water resistant and slip resistant. Easy to apply and easy to remove.

USAGE

For use in all resilient tile, sealed wood, concrete, marble and terrazzo floors, etc.

DIRECTIONS

Thoroughly strip floor of all old finish and dirt, using a quality stripper at recommended dilutions. Surface must be free of all old wax and finishes. Rinse floor thoroughly and allow to dry completely.

Apply one or two coats using a new mop and clean equipment. New mops should be washed in clean water before initial use.

Allow 20 minutes drying time between coats. Because of its high solid content, this product acts as a sealer on porous floors.

Daily maintenance consists of damp mopping and/or spray buffing.

PRODUCT SPECIFICATIONS

APPEARANCE	Milk white liquid
FILM COLOR	Color free, even after extended use
VISCOSITY @ 77°F cps	Less than A-1 (Gardner-Holt)
PERCENT SOLIDS	18% +/- 0.5%
FLASH POINT	None
pH	7.5 - 8.0
RECOATING TIME	20 minutes
WALK ON TIME	20 - 30 minutes
LEVELING PROPERTIES	Excellent
UL SCUFF RESISTANCE	Outstanding
BLACK MARK RESISTANCE	Outstanding
ABRASION RESISTANCE	Outstanding
SLIP RESISTANCE	Excellent
PACKAGING	55- 35- 15 Gallon drums 5 Gallon pails Cases of 6/1 gallon jugs

SAFETY INFORMATION

CAUTION

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

Use only as directed. Do not mix with anything since harmful conditions and poor performance could result.

Do not pour unused product back into container, it may contaminate the product.

All floors are slippery when wet. To prevent falls, exercise care when working and block off traffic areas with "WET FLOOR" or "CAUTION" signs until floor is completely dry.

Quality  Chemical

1835 N.E. 144th Street, North Miami, Florida 33181
(305) 944-2837 • (888) 355-5540 • Fax (305) 944-6857
www.QualityChemical.com